

Deleted Models in this Catalog

Following models were deleted in this latest version of catalog. However, these models are not discontinued product. Please contact us for further assistance if necessary.

■ DC Fan

Size	Model No.	Frame material	Rated Voltage [V]	Operating Voltage Range [V]	Rated Current [A]	Rated Input [W]	Rated Speed [min ⁻¹]	Max. Airflow [m ³ /min] [CFM]	Max. Static Pressure [Pa] [inchH ₂ O]	SPL [dB(A)]	Operating Temperature [°C]	Life Expectancy [h]		
92 × 92 × 25mm	109P0912J401	Plastics	12	6 to 13.8	0.56	6.72	4,300	2.03 71.6	92.2 0.37	47	- 20 to + 60	40,000		
92 × 92 × 25mm	109P0912W401	Plastics	12	6 to 16	0.21	2.52	2,850	1.45 51.2	45 0.181	33	- 20 to + 70	40,000		
92 × 92 × 25mm	109P0912H401	Plastics	12	10.2 to 13.8	0.21	2.52	2,850	1.45 51.2	45 0.181	33	- 20 to + 70	40,000		
92 × 92 × 25mm	109P0912F401	Plastics	12	10.2 to 13.8	0.14	1.68	2,450	1.24 43.8	32.3 0.130	30	- 20 to + 70	40,000		
92 × 92 × 25mm	109P0912M401	Plastics	12	10.2 to 13.8	0.1	1.2	2,100	1.04 36.7	23.5 0.094	27	- 20 to + 70	40,000		
92 × 92 × 25mm	109P0912L401	Plastics	12	10.2 to 13.8	0.07	0.84	1,700	0.8 28.3	16.6 0.067	23	- 20 to + 70	40,000		
92 × 92 × 25mm	109P0924W401	Plastics	24	12 to 30	0.12	2.88	2,850	1.45 51.2	45 0.181	33	- 20 to + 70	40,000		
92 × 92 × 25mm	109P0924H401	Plastics	24	20.4 to 27.6	0.12	2.88	2,850	1.45 51.2	45 0.181	33	- 20 to + 70	40,000		
92 × 92 × 25mm	109P0924F401	Plastics	24	20.4 to 27.6	0.08	1.92	2,450	1.24 43.8	32.3 0.130	30	- 20 to + 70	40,000		
92 × 92 × 25mm	109P0924M401	Plastics	24	20.4 to 27.6	0.06	1.44	2,100	1.04 36.7	23.5 0.094	27	- 20 to + 70	40,000		
92 × 92 × 25mm	109P0924L401	Plastics	24	20.4 to 27.6	0.05	1.2	1,700	0.8 28.3	16.6 0.067	23	- 20 to + 70	40,000		
92 × 92 × 25mm	109P0948H401	Plastics	48	43 to 53	0.06	2.88	2,850	1.45 51.2	45 0.181	33	- 20 to + 70	40,000		
φ 200mm × 70mm	109E2024S001	Aluminum	24	21.6 to 26.4	1.9	45.6	3,200	10.45 369	287.1 1.153	57	- 10 to + 70	40,000		
φ 200mm × 70mm	109E2024H001	Aluminum	24	20.4 to 27.6	1.0	24	2,600	8.2 289.5	192 0.771	51	- 10 to + 70	40,000		
φ 200mm × 70mm	109E2024AS001	Aluminum	24	21.6 to 26.4	1.9	45.6	3,200	10.45	369	287.1	1.153	57	- 10 to + 70	40,000
					1.45	34.8	2,800	9	317.8	215.6	0.865	54		
φ 200mm × 70mm	109E2024MH001	Aluminum	24	20.4 to 27.6	1.0	24	2,600	8.2	289.5	192	0.771	51	- 10 to + 70	40,000
					0.63	15.12	2,100	6.7	236.6	115.4	0.463	45		

■ Counter Rotating Fan

Size	Model No.	Frame material	Rated Voltage [V]	Operating Voltage Range [V]	Rated Current [A]	Rated Input [W]	Rated Speed [min ⁻¹]		Max. Airflow [m ³ /min] [CFM]		Max. Static Pressure [Pa] [inchH ₂ O]		SPL [dB(A)]	Operating Temperature [°C]	Life Expectancy [h]
							Inlet	Outlet							
40 × 40 × 56mm	9CRA0412K501	Plastics	12	10.8 to 12.6	1.8	21.6	17,000	13,000	0.95 33.5	650 2.61	65	- 20 to + 60	40,000		
40 × 40 × 56mm	9CRA0412J501	Plastics	12	10.8 to 13.2	1.4	16.8	15,800	12,200	0.9 31.8	570 2.29	62	- 20 to + 70	40,000		
40 × 40 × 56mm	9CRA0412G501	Plastics	12	10.8 to 13.2	1.0	12	14,000	10,400	0.77 27.2	435 1.75	59	- 20 to + 70	40,000		
60 × 60 × 76mm	9CR0612S001	Plastics	12	10.8 to 13.2	3.2	38.4	11,500	7,000	2.26 80	550 2.21	66	- 10 to + 60	40,000		
60 × 60 × 76mm	9CR0612H001	Plastics	12	10.8 to 13.2	2.7	32.4	10,300	6,500	1.98 70	450 1.81	64	- 10 to + 60	40,000		
80 × 80 × 80mm	9CR0812S801	Plastics	12	10.8 to 13.2	5.5	66.0	8,000	5,300	4.53 160	520 2.09	71	- 10 to + 60	40,000		
80 × 80 × 80mm	9CR0812H801	Plastics	12	10.8 to 13.2	3.6	43.2	7,000	4,600	3.97 140	400 1.61	68	- 10 to + 60	40,000		

Size	Model No.	Frame material	Rated Voltage [V]	PWM Frequency [kHz]	Rated Current [A]	Rated Speed [min ⁻¹]		Max. Airflow [m ³ /min] [CFM]		Max. Static Pressure [Pa] [inchH ₂ O]		SPL [dB(A)]	Expected Life [h]
						Duty Cycle 0%	Duty Cycle 100%						
60 × 60 × 76mm	9CR0612P0S03	Plastics	12	25.0	3.2	Inlet : 1,300 outlet : 800	Inlet : 11,500 outlet : 7,000	2.26	79.8	550	2.21	66	40,000
	9CR0612P0H03	Plastics	12	25.0	2.7	Inlet : 1,200 outlet : 800	Inlet : 10,300 outlet : 6,500	1.98	69.91	450	1.81	64	40,000
80 × 80 × 80mm	9CR0848P8S03	Plastics	48	25.0	1.29	Inlet : 2,000 outlet : 1,300	Inlet : 8,000 outlet : 5,300	4.53	159.95	520	2.09	71	40,000

Deleted models in this catalog

Splash Proof Fan

Size	Model No.	Frame material	Rated Voltage [V]	Operating Voltage Range [V]	Rated Current [A]	Rated Input [W]	Rated Speed [min ⁻¹]	Max. Airflow [m ³ /min] [CFM]	Max. Static Pressure [Pa] [inchH ₂ O]	SPL [dB(A)]	Operating Temperature [°C]	Life Expectancy [h]
80 × 80 × 25mm	109W0812H401-U	Aluminum	12	10.2 to 13.8	0.18	2.16	3,000	1.06 37.4	39.2 0.157	32	-10 to +70	100,000
80 × 80 × 25mm	109W0812F401-U	Aluminum	12	10.2 to 13.8	0.14	1.68	2,700	0.93 32.8	32.3 0.130	29	-10 to +70	100,000
80 × 80 × 25mm	109W0812M401-U	Aluminum	12	10.2 to 13.8	0.10	1.20	2,400	0.83 29.3	26.5 0.106	26	-10 to +70	100,000
80 × 80 × 25mm	109W0812L401-U	Aluminum	12	10.2 to 13.8	0.08	0.96	1,900	0.63 22.2	16.67 0.067	22	-10 to +70	100,000
80 × 80 × 25mm	109W0824H401-U	Aluminum	24	20.4 to 27.6	0.09	2.16	3,000	1.06 37.4	39.2 0.157	32	-10 to +70	100,000
80 × 80 × 25mm	109W0824F401-U	Aluminum	24	20.4 to 27.6	0.08	1.92	2,700	0.93 32.8	32.3 0.130	29	-10 to +70	100,000
80 × 80 × 25mm	109W0824M401-U	Aluminum	24	20.4 to 27.6	0.07	1.68	2,400	0.83 29.3	26.5 0.106	26	-10 to +70	100,000
80 × 80 × 25mm	109W0824L401-U	Aluminum	24	20.4 to 27.6	0.05	1.20	1,900	0.63 22.2	16.67 0.067	22	-10 to +70	100,000
80 × 80 × 25mm	109W0848H401-U	Aluminum	48	40.8 to 55.2	0.06	2.88	3,150	1.10 38.8	43.1 0.173	34	-10 to +70	100,000
92 × 92 × 25mm	109W0912H401-U	Aluminum	12	10.2 to 13.8	0.21	2.52	2,850	1.38 48.7	45.1 0.181	33	-10 to +70	100,000
92 × 92 × 25mm	109W0912F401-U	Aluminum	12	10.2 to 13.8	0.14	1.68	2,450	1.18 41.7	32.3 0.130	30	-10 to +70	100,000
92 × 92 × 25mm	109W0912M401-U	Aluminum	12	10.2 to 13.8	0.11	1.32	2,100	1.01 35.7	23.5 0.094	27	-10 to +70	100,000
92 × 92 × 25mm	109W0912L401-U	Aluminum	12	10.2 to 13.8	0.08	0.96	1,700	0.80 28.2	16.7 0.067	23	-10 to +70	100,000
92 × 92 × 25mm	109W0924H401-U	Aluminum	24	20.4 to 27.6	0.12	2.88	2,850	1.38 48.7	45.1 0.181	33	-10 to +70	100,000
92 × 92 × 25mm	109W0924F401-U	Aluminum	24	20.4 to 27.6	0.08	1.92	2,450	1.18 41.7	32.3 0.130	30	-10 to +70	100,000
92 × 92 × 25mm	109W0924M401-U	Aluminum	24	20.4 to 27.6	0.06	1.44	2,100	1.01 35.7	23.5 0.094	27	-10 to +70	100,000
92 × 92 × 25mm	109W0924L401-U	Aluminum	24	20.4 to 27.6	0.05	1.20	1,700	0.80 28.2	16.7 0.067	23	-10 to +70	100,000
92 × 92 × 25mm	109W0948H401-U	Aluminum	48	40.8 to 55.2	0.06	2.88	2,850	1.38 48.7	45.1 0.181	33	-10 to +70	100,000

Long Life Fan

Size	Model No.	Frame material	Rated Voltage [V]	Operating Voltage Range [V]	Rated Current [A]	Rated Input [W]	Rated Speed [min ⁻¹]	Max. Airflow [m ³ /min] [CFM]	Max. Static Pressure [Pa] [inchH ₂ O]	SPL [dB(A)]	Operating Temperature [°C]	Life Expectancy [h]
60 × 60 × 25mm	109L0612G401	Aluminum	12	10.2 to 13.8	0.24	2.88	5,600	0.78 27.5	87.3 0.35	39	-20 to +70	100,000
60 × 60 × 25mm	109L0612S401	Aluminum	12	10.2 to 13.8	0.17	2.04	4,600	0.65 23.0	56.8 0.228	33	-20 to +70	100,000
60 × 60 × 25mm	109L0612H401	Aluminum	12	10.2 to 13.8	0.11	1.32	3,800	0.53 18.7	40.2 0.161	28	-20 to +70	100,000
60 × 60 × 25mm	109L0612F401	Aluminum	12	10.2 to 13.8	0.09	1.08	3,200	0.44 15.5	29.4 0.118	24	-20 to +70	100,000
60 × 60 × 25mm	109L0612M401	Aluminum	12	10.2 to 13.8	0.06	0.72	2,600	0.36 12.7	19.6 0.079	20	-20 to +70	100,000
60 × 60 × 25mm	109L0624D401	Aluminum	24	20.4 to 27.6	0.12	2.88	5,150	0.72 25.4	73.8 0.296	37	-20 to +70	100,000
60 × 60 × 25mm	109L0624S401	Aluminum	24	20.4 to 27.6	0.08	1.92	4,600	0.65 23.0	56.8 0.230	33	-20 to +70	100,000
60 × 60 × 25mm	109L0624H401	Aluminum	24	20.4 to 27.6	0.06	1.44	3,800	0.53 18.7	40.2 0.161	28	-20 to +70	100,000
60 × 60 × 25mm	109L0624F401	Aluminum	24	20.4 to 27.6	0.05	1.20	3,200	0.44 15.5	29.4 0.118	24	-20 to +70	100,000
60 × 60 × 25mm	109L0624M401	Aluminum	24	20.4 to 27.6	0.04	0.96	2,600	0.36 12.7	19.6 0.079	20	-20 to +70	100,000
60 × 60 × 25mm	109L0648G401	Aluminum	48	40.8 to 55.2	0.07	3.36	5,600	0.78 27.5	87.3 0.35	39	-20 to +60	80,000
60 × 60 × 25mm	109L0648H401	Aluminum	48	40 to 53	0.04	1.92	3,800	0.53 18.7	40.2 0.161	28	-20 to +70	100,000
80 × 80 × 25mm	109L0812S401	Aluminum	12	10.2 to 13.8	0.26	3.12	3,400	1.2 42.4	50 0.2	37	-20 to +70	100,000
80 × 80 × 25mm	109L0812H401	Aluminum	12	10.2 to 13.8	0.18	2.16	3,000	1.06 37.4	39.2 0.157	32	-20 to +70	100,000
80 × 80 × 25mm	109L0812F401	Aluminum	12	10.2 to 13.8	0.14	1.68	2,700	0.93 32.8	32.3 0.130	29	-20 to +70	100,000
80 × 80 × 25mm	109L0812M401	Aluminum	12	10.2 to 13.8	0.1	1.2	2,400	0.83 29.3	26.5 0.106	26	-20 to +70	100,000
80 × 80 × 25mm	109L0812L401	Aluminum	12	10.2 to 13.8	0.08	0.96	1,900	0.63 22.2	16.7 0.067	22	-20 to +70	100,000
80 × 80 × 25mm	109L0824S401	Aluminum	24	20.4 to 27.6	0.11	2.64	3,400	1.2 42.4	50 0.2	37	-20 to +70	100,000
80 × 80 × 25mm	109L0824H401	Aluminum	24	20.4 to 27.6	0.09	2.16	3,000	1.06 37.4	39.2 0.157	32	-20 to +70	100,000
80 × 80 × 25mm	109L0824F401	Aluminum	24	20.4 to 27.6	0.08	1.92	2,700	0.93 32.8	32.3 0.130	29	-20 to +70	100,000
80 × 80 × 25mm	109L0824M401	Aluminum	24	20.4 to 27.6	0.07	1.68	2,400	0.83 29.3	26.5 0.106	26	-20 to +70	100,000
80 × 80 × 25mm	109L0824L401	Aluminum	24	20.4 to 27.6	0.05	1.2	1,900	0.63 22.2	16.7 0.067	22	-20 to +70	100,000
80 × 80 × 25mm	109L0848H401	Aluminum	48	40.8 to 55.2	0.06	2.88	3,150	1.1 38.8	43.1 0.173	34	-20 to +70	100,000
92 × 92 × 25mm	109L0912S401	Aluminum	12	10.2 to 13.8	0.32	3.84	3,500	1.69 59.7	66.6 0.267	39	-20 to +70	100,000
92 × 92 × 25mm	109L0912H401	Aluminum	12	10.2 to 13.8	0.21	2.52	2,850	1.38 48.7	45.1 0.181	33	-20 to +70	100,000
92 × 92 × 25mm	109L0912F401	Aluminum	12	10.2 to 13.8	0.14	1.68	2,450	1.18 41.7	32.3 0.130	30	-20 to +70	100,000
92 × 92 × 25mm	109L0912M401	Aluminum	12	10.2 to 13.8	0.11	1.32	2,100	1.01 35.7	23.5 0.094	27	-20 to +70	100,000
92 × 92 × 25mm	109L0912L401	Aluminum	12	10.2 to 13.8	0.08	0.96	1,700	0.80 28.2	16.7 0.067	23	-20 to +70	100,000
92 × 92 × 25mm	109L0924H401	Aluminum	24	20.4 to 27.6	0.12	2.88	2,850	1.38 48.7	45.1 0.181	33	-20 to +70	100,000
92 × 92 × 25mm	109L0924F401	Aluminum	24	20.4 to 27.6	0.08	1.92	2,450	1.18 41.7	32.3 0.130	30	-20 to +70	100,000
92 × 92 × 25mm	109L0924M401	Aluminum	24	20.4 to 27.6	0.06	1.44	2,100	1.01 35.7	23.5 0.094	27	-20 to +70	100,000
92 × 92 × 25mm	109L0924L401	Aluminum	24	20.4 to 27.6	0.05	1.2	1,700	0.80 28.2	16.7 0.067	23	-20 to +70	100,000
92 × 92 × 25mm	109L0948C401	Aluminum	48	43 to 53	0.1	4.8	3,400	1.65 58.3	64.2 0.258	38	-20 to +70	80,000
92 × 92 × 25mm	109L0948H401	Aluminum	48	40.8 to 55.2	0.06	2.88	2,850	1.38 48.7	45.1 0.181	33	-20 to +70	100,000
120 × 120 × 38mm	9LB1212H101	Aluminum	12	10.2 to 13.8	0.39	4.68	2,600	2.9 102.4	67.62 0.272	39	-20 to +70	200,000
120 × 120 × 38mm	9LB1212M101	Aluminum	12	10.2 to 13.8	0.22	2.64	2,000	2.2 77.7	42.14 0.169	32	-20 to +70	200,000
120 × 120 × 38mm	9LB1224S101	Aluminum	24	20.4 to 27.6	0.46	11.04	3,500	3.88 137.0	120.8 0.485	48	-20 to +70	100,000
120 × 120 × 38mm	9LB1224H101	Aluminum	24	20.4 to 27.6	0.19	4.56	2,600	2.9 102.4	67.62 0.272	39	-20 to +70	200,000
120 × 120 × 38mm	9LB1224M101	Aluminum	24	20.4 to 27.6	0.11	2.64	2,000	2.2 77.7	42.14 0.169	32	-20 to +70	200,000
120 × 120 × 38mm	9LB1248H101	Aluminum	48	40.8 to 55.2	0.11	5.28	2,600	2.9 102.4	67.62 0.272	39	-20 to +70	200,000
120 × 120 × 38mm	9LB1248M101	Aluminum	48	40.8 to 55.2	0.06	2.88	2,000	2.2 77.7	42.14 0.169	32	-20 to +70	200,000

Thermally Controlled Fan

Size	Model No.	Frame material	Rated Voltage [V]	Operating Voltage Range [V]	Rated Current [A]	Rated Input [W]	Rated Speed [min ⁻¹]	Max. Airflow [m ³ /min] [CFM]	Max. Static Pressure [Pa] [inchH ₂ O]	SPL [dB(A)]	Operating Temperature [°C]	Life Expectancy [h]
52 × 52 × 15mm	109P0512T7H12	Plastics	12	10.2 to 13.8	0.13	1.56	4,600	0.255 9.0	31.9 0.128	27	- 10 to + 70	60,000
					0.09	1.08	2,300	0.13 4.6	8.8 0.035	17		
52 × 52 × 15mm	109P0512T7H122	Plastics	12	10.2 to 13.8	0.13	1.56	4,900	0.27 9.5	36.2 0.145	28	- 10 to + 70	60,000
					0.09	1.08	2,400	0.14 4.9	9.6 0.039	17		
60 × 60 × 15mm	109P0612T7H12	Plastics	12	10.2 to 13.8	0.12	1.44	4,100	0.4 14.1	38.2 0.153	32	- 10 to + 70	60,000
					0.08	0.96	2,050	0.2 7.1	9.3 0.037	18		
60 × 60 × 15mm	109P0612T7H122	Plastics	12	10.2 to 13.8	0.12	1.44	4,300	0.42 14.8	42.0 0.169	32	- 10 to + 70	60,000
					0.08	0.96	2,100	0.2 7.0	9.7 0.039	18		
60 × 60 × 20mm	109P0612T6H12	Plastics	12	10.2 to 13.8	0.15	1.8	4,200	0.42 14.8	31.9 0.128	31	- 10 to + 70	60,000
					0.10	1.2	2,100	0.21 7.4	8.8 0.035	21		
60 × 60 × 20mm	109P0612T6H122	Plastics	12	10.2 to 13.8	0.15	1.8	4,400	0.44 15.5	35.0 0.141	33	- 10 to + 70	60,000
					0.10	1.2	2,150	0.22 7.8	9.2 0.037	21		
60 × 60 × 25mm	109R0612T4H12 109R0612T4H121	Plastics	12	10.2 to 13.8	0.13	1.56	3,800	0.53 18.7	40.2 0.161	28	- 10 to + 60	60,000
					0.10	1.20	1,900	0.26 9.2	9.8 0.039	15		
60 × 60 × 25mm	109R0612T4H122 109R0612T4H123	Plastics	12	10.2 to 13.8	0.13	1.56	3,950	0.55 19.4	41.8 0.168	28	- 10 to + 60	60,000
					0.10	1.20	1,950	0.27 9.5	10.3 0.041	15		
80 × 80 × 20mm	109P0812T6H12	Plastics	12	10.2 to 13.8	0.18	2.16	2,900	0.84 29.7	29.4 0.118	31	- 10 to + 60	60,000
					0.1	1.2	1,450	0.42 14.8	7.4 0.030	20		
80 × 80 × 20mm	109P0812T6H122	Plastics	12	10.2 to 13.8	0.18	2.16	3,050	0.88 31.0	32.5 0.131	32	- 10 to + 60	60,000
					0.1	1.2	1,450	0.42 14.8	7.4 0.030	20		
80 × 80 × 25mm	109R0812T4H12 109R0812T4H121	Plastics	12	10.2 to 13.8	0.14	1.68	2,900	1.03 36.4	35.3 0.142	29	- 10 to + 60	60,000
					0.09	1.08	1,450	0.51 18.0	8.8 0.035	14		
80 × 80 × 25mm	109R0812T4H122 109R0812T4H123	Plastics	12	10.2 to 13.8	0.14	1.68	3,000	1.07 37.8	37.7 0.151	29	- 10 to + 60	60,000
					0.09	1.08	1,450	0.51 18.0	8.8 0.035	14		
92 × 92 × 25mm	109P0912T4H12 109P0912T4H121	Plastics	12	10.2 to 13.8	0.2	2.4	2,850	1.45 51.2	45.1 0.181	33	- 10 to + 60	40,000
					0.1	1.2	1,400	0.71 25.0	11.3 0.045	18		
92 × 92 × 25mm	109P0912T4H122 109P0912T4H123	Plastics	12	10.2 to 13.8	0.2	2.4	3,000	1.52 53.7	50.0 0.201	35	- 10 to + 60	40,000
					0.1	1.2	1,400	0.71 25.0	11.3 0.045	18		
120 × 120 × 25mm	109P1212T4H12 109P1212T4H121	Plastics	12	10.2 to 13.8	0.55	6.6	2,800	2.5 88.3	53.9 0.216	40	- 10 to + 60	40,000
					0.22	2.64	1,400	1.25 44.1	13.7 0.055	25		
120 × 120 × 25mm	109P1212T4H122 109P1212T4H123	Plastics	12	10.2 to 13.8	0.55	6.6	2,800	2.5 88.3	53.9 0.216	40	- 10 to + 60	40,000
					0.22	2.64	1,400	1.25 44.1	13.7 0.055	25		
120 × 120 × 38mm	109R1212T1H12 109R1212T1H121	Plastics	12	10.2 to 13.8	0.48	5.75	2,600	2.9 102.4	64.7 0.260	39	- 10 to + 60	40,000
					0.23	2.76	1,300	1.4 49.4	16.2 0.065	24		
120 × 120 × 38mm	109R1212T1H122 109R1212T1H123	Plastics	12	10.2 to 13.8	0.48	5.75	2,600	2.9 102.4	64.7 0.260	39	- 10 to + 60	40,000
					0.23	2.76	1,300	1.4 49.4	16.2 0.065	24		

Blower

Size	Model No.	Frame material	Rated Voltage [V]	Operating Voltage Range [V]	Rated Current [A]	Rated Input [W]	Rated Speed [min ⁻¹]	Max. Airflow [m ³ /min] [CFM]	Max. Static Pressure [Pa] [inchH ₂ O]	SPL [dB(A)]	Operating Temperature [°C]	Life Expectancy [h]
120 × 32mm	109BF12HC2	Plastics	12	10.2 to 13.8	0.6	7.2	2,400	0.78 27.5	175.4 0.704	52	- 20 to + 60	40,000
120 × 32mm	109BF12MC2	Plastics	12	10.2 to 13.8	0.32	3.84	1,900	0.61 21.5	109.8 0.441	44	- 20 to + 60	40,000
120 × 32mm	109BF24HC2	Plastics	24	20.4 to 27.6	0.3	7.2	2,400	0.78 27.5	175.4 0.704	52	- 20 to + 60	40,000
120 × 32mm	109BF24MC2	Plastics	24	20.4 to 27.6	0.16	3.84	1,900	0.61 21.5	109.8 0.441	44	- 20 to + 60	40,000

• Storage temperature is -30°C to +70°C .